Cat® Ball Bearing Grease

For Use in High Speed Ball & Roller Bearing Applications

NLGI 2



Discover the Difference

Formulated with polyurea thickener and corrosion inhibitors, Cat® Ball Bearing Grease provides excellent lubrication in ball and roller bearings operating over a broad temperature range. Cat Ball Bearing Grease is developed, tested and approved by Caterpillar to meet the same high standards as Genuine Cat Parts.

High-Stress Performance—Provides outstanding protection at high speeds (10,000 rpm and greater) and the high temperatures (160°C/320°F) associated with high-speeds.

Increased Component Life—Heat resistance provides improved protection, reducing component wear rates.





Cat® Ball Bearing Grease

Grease Selection Guide

Cat Extreme Application Grease 1 NLGI 1

With 5% Moly

(-20 to 140°C/-4 to 284°F)

Cat Extreme Application Grease - Desert NLGI 2 (Temps up to 140°C/284°F)

With 5% Moly

Cat Prime Application Grease NLGI 2 (-20 to 140°C/-4 to 284°F)

Cat Ball Bearing Grease NLGI 2 Temps above -20°C/-4°F)

Without Moly



Cat Extreme Application Grease - Arctic NLGI 0.5 Temps down to -50°C/58°F)

With 5% Moly

Med Load &

Cat Utility Grease NLGI 2 (-20 to 140°C/-4 to 284°F) Without Molv

Low Load & Low Speed

Low Load & **High Speed**

Working Environment High Load & High Speed

High Temp

Low Temp

Med Speed

Daa	 	Haa
Kec	THIL	IUS(A

Cat Ball Bearing Grease can be used for high-speed ball-, needle- and sealedbearing applications such as:

- electric motors fan drives
- starters alternators
- generators

It can also be used in automotive and industrial applications, especially where equipment is operated intermittently in severe conditions.

Health and Safety

For information on proper use for health, safety and environment, please refer to the Material Safety Data Sheet (MSDS). Read and understand the MSDS before using this product. Always observe good hygiene measures. For a copy of the MSDS, contact us or visit the web at

* All temperatures are Operating Temperatures				
Typical Properties				
NLGI	2			
Color	Blue			
Operating Temperature Range, °C	-20 to +160			
Operating Temperature Range, °F	-4 to +320			
Base Oil Type	Mineral			
ASTM D445 Base Oil Viscosity 40°C, mm²/s	115			
ASTM D445 Base Oil Viscosity 100°C, mm²/s	12.2			
Thickener Type	Polyurea			
ASTM D2265 Dropping point, °C	270			
ASTM D217 Penetration, worked 60, mm/10	280			
ASTM D1743 Rust prevention	Pass			
ASTM D4048 Copper corrosion	1b			
ASTM D1264 Water wash-out, 79°C, mass %	1.9			

The values shown are typical values and should not be used as quality control parameters to either accept or reject product. Specifications are subject to change without notice.

CAT DEALERS DEFINE WORLD-**CLASS PRODUCT SUPPORT.**

We offer you the right parts and service solutions, when and where you need them.

The Cat Dealer network of highly trained experts keeps your fleet up and running to maximize your equipment investment.

BUILT FOR IT.



PEHJ0405

